

PRODUCT DETAILS

| PRODUCT CODE | MF78 | |
|----------------|---|--|
| WARRANTY | 40 months (Private Passenger Use) * | |
| CHARACTERISTIC | Sealed Maintenance Free Lead Acid Battery | |
| GROUP SIZE | G65 | |
| ASE AND LID | Material : Polypropylene (PP) | |
| | Handle : 1 pc Plastic | |
| | Ledges : Front Ledge (FL) | |
| | Venting Centralized system with | |
| | System Degassing vents on sides | |



DIMENSIONS, WEIGHT, AND LAYOUT


| OVERALL DIMENSIONS | METRIC |
|------------------------|--------|
| LENGTH, mm | 258 |
| WIDTH, mm | 176 |
| CASE HEIGHT, mm | 183 |
| TOTAL HEIGHT, mm | 183 |
| APPROXIMATE WEIGHT, kg | 17.52 |


| TERMINAL DATA | METRIC |
|---------------------|-------------------|
| TYPE | Side Terminal |
| TERMINAL HEIGHT, mm | - |
| BOTTOM DIAMETER, mm | - |
| TAPER | - |
| POLARITY | D (Positive Left) |

CAPACITY SPECIFICATIONS

| COLD CRANKING AMPS (CCA) | 760 CCA | |
|------------------------------------|----------|--|
| AMPERE-HOUR AT 20-HOUR CAPACITY | 70 Ah | |
| RESERVE CAPACITY (RC) | 120 mins | |

| MAX CHARGING VOLTAGE | 14.8 V at 25°C |
|---------------------------|---|
| FLOAT CHARGING VOLTAGE | 13.5 V – 13.8 V at 25°C |
| OPERATING TEMPERATURE | -40°C to 80° C** Optimal Temperature: 25° C \pm 5° C |







^{*}Warranty terms and conditions apply.
**Based on normal engine bay temperature.