




24 Months Warranty

PART NUMBER	U1R-AGM	
CHARACTERISTIC	Valve Regulated Lead Acid (Absorbent Glass Mat)	
GROUP SIZE	GU1	
CASE AND LID	Material	Polypropylene (PP)
	Handle	2-pc PP handle
	Case Colour	Black Casing
	Lid Colour	Black Lid
	Ledge / Hold-down	No Ledge (NL)
	Vent	Centralized venting

DIMENSIONAL SPECIFICATIONS

OVERALL DIMENSIONS	METRIC (mm)
LENGTH	195
WIDTH	125
HEIGHT (bottom to top cover)	156
TOTAL HEIGHT (bottom to top of terminal)	176
NOMINAL WEIGHT	6.65 kg

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	U1 (OLT)	U1 (OLT)
TERMINAL HEIGHT (mm)	20.0	20.0
BOTTOM DIAMETER (mm)	-	-
TAPER	-	-
POLARITY		

DIMENSIONAL SPECIFICATIONS

COLD CRANKING AMPS (CCA)	350 CCA
	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec
CAPACITY (RC)	40 mins
	Test reference: AS60095.1: 2022 25 Amps DCH at 10.5 V cut-off voltage

AMPERE-HOUR (20-HOUR CAPACITY)	21 AH
	Test reference: AS60095.1: 2022
	Rated AH DCH at 10.5 V cut-off
PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design
ELECTROLYTE	36% H2SO4 at 15°C

