

SUPERCHARGE[®] **BATTERIES**



STOP START HYBRID AUXILIARY



**Designed to withstand
more punishment. Built to last.**

- Exceeds OE² performance and safety specifications for stop-start vehicles
- Built to withstand frequent discharge requirements of stop-start engines
- Engineered with hardened framed plates and corrosion-resistant alloys
- Advanced dense and compact battery construction
- High efficiency energy output and recovery
- Vibration-resistant design


Reliable, Long service life, Built to last.

START-STOP RANGE

TYPE	NOMINAL VOLTAGE V	TECH	CCA (EN)	RC (min)	AH	OVERALL DIMENSION (mm)				WET WEIGHT (kg)	ASSEMBLY	POST TYPE	PRIVATE WARRANTY (months)	COMMERCIAL WARRANTY (months)
						L	W	H	TH					
ABSORBED GLASS MAT - AGM														
MF44HSS	12	AGM SS	540	80	50	208	175	190	190	15.40	C	STD	36	12
MF55HSS	12	AGM SS	680	100	60	242	175	190	190	18.80	C	STD	36	12
MF66HSS	12	AGM SS	760	120	70	278	175	190	190	21.30	C	STD	36	12
MF77HSS	12	AGM SS	800	140	80	315	175	190	190	24.00	C	STD	36	12
MF77HSSR	12	AGM SS	800	140	80	315	175	190	190	24.00	D	STD	36	12
MF88HSS	12	AGM SS	850	160	92	353	175	190	190	26.50	C	STD	36	12
MF95HSS	12	AGM SS	950	205	105	393	174	190	190	28.50	C	STD	36	12
ENHANCED FLOODED BATTERIES - EFB														
MFB24EF	12	EFB SS	475	90	55	238	129	205	225	13.00	C	STD	36	12
MFD23EF	12	EFB SS	685	112	67	231	172	200	220	18.00	C	STD	36	12
MFD23EFR	12	EFB SS	685	112	67	231	172	200	220	18.00	D	STD	36	12
MFD26EF	12	EFB SS	700	130	75	258	172	200	220	20.00	C	STD	24	12
MFD31EF	12	EFB SS	830	155	95	303	172	200	220	23.00	C	STD	24	12
MF55HEF	12	EFB SS	660	100	60	245	175	190	190	16.70	C	STD	24	12
MF66EF	12	EFB SS	660	105	65	277	174	175	175	16.80	C	STD	24	12
MF66HEF	12	EFB SS	750	120	70	278	175	190	190	19.10	C	STD	24	12
MF77EF	12	EFB SS	780	150	75	315	174	175	175	19.50	C	STD	24	12
MF77HEF	12	EFB SS	800	150	80	315	174	190	190	21.20	C	STD	24	12
ENI50EFL	12	EFB SS	1000	360	180	510	222	196	217	47.40	E	STD	24	24
HYBRID AUXILIARY AGM														
B20R-AGM	12	AGM	340	-	35	197	129	203	227	12.50	D	PT	36	12
B24R-AGM	12	AGM	370	-	45	236	125	200	224	13.00	D	PT	36	12
D23R-AGM	12	AGM	550	-	50	220	170	200	220	15.10	D	STD	36	12

ABBREVIATIONS & BATTERY ASSEMBLIES

DFA	Dual Fit Aligned Terminals	ST	Side Terminal
DFP	Dual Fit Parallel Terminals	STD	Standard Terminal
DST	Dual System Terminals	TS	Top Stud Terminal
PT	Pencil Terminal		



NEW ZEALAND

AUCKLAND

72B Highbrook Dr East Tamaki

Auckland 09 975 8900

HAMILTON

61 Mahana Rd Tr Rapa

Hamilton 07 849 2002

WELLINGTON

33 Pito-One Road, Korokoro, Lower Hutt

Wellington 04 566 1054

NELSON

3/9 Nayland Road, Stoke

Nelson 03 547 4008

CHRISTCHURCH

3B/198 Springs Road, Hornby

Christchurch 03 349 9650

0800 188 122

www.superchargebatteries.co.nz

