

★ SUPERCHARGE[®] **BATTERIES**

SILVERPLUS



Designed to exceed original equipment requirement. Longer Life.

- > Built with More Lead-Calcium Tropicalised* Power Plates
- > Formulated for high state of charge retention
- > Advanced dense and compact battery construction
- > Assembled using hardened alloys and intercell connections
- > Fully-sealed Maintenance-Free battery
- > High efficiency electrical flow design
- > Formulated with high purity lead and electrolyte

Reliable, Long service life, Built to last.

* Design which aids in heat dissipation inside the battery, thereby reducing life degradation due to extreme heat of under-bonnet conditions.

superchargebatteries.co.nz | 0800 188 122

SILVERPLUS

TYPE	NOMINAL VOLTAGE V	CCA (SAE)	RC (min)	AH (20HR)	OVERALL DIMENSION (mm)			WET WEIGHT (kg)	ASSEMBLY	POST TYPE	BASE WARRANTY (Private Use)	EXTENDED WARRANTY (Private Use)	COMMERCIAL USE WARRANTY
					L	W	TH						
POPULAR AUTOMOTIVE													
SMF43	12	320	43	35	238	138	212	10.69	H	DFP	36	40	18
SMF57	12	550	95	50	237	171	203	14.67	D	STD	36	40	18
SMF58	12	550	95	50	237	171	208	15.03	C	DFP	36	40	18
SMF58VT	12	550	95	50	228	171	203	14.67	C	STD	36	40	18
JAPANESE AUTOMOTIVE													
SMFNS40ZLX	12	350	62	40	196	128	219	9.16	C	PT	36	40	18
SMFNS40ZALX	12	350	62	40	196	128	219	9.16	C	STD	36	40	18
SMFNS40ZX	12	350	62	40	196	128	219	9.16	D	PT	36	40	18
SMFNS40ZAX	12	350	62	40	196	128	219	9.16	D	STD	36	40	18
SMFNS60R	12	480	82	52	236	128	219	12.96	D	PT	36	40	18
SMFNS60L	12	480	82	52	236	128	219	12.96	C	PT	36	40	18
SMFNS60RS	12	480	82	52	236	128	219	12.96	D	STD	36	40	18
SMFNS60LS	12	480	82	52	236	128	219	12.96	C	STD	36	40	18
SMF50D20L	12	450	80	50	200	174	221	13.79	C	STD	36	40	18
SMF55D23R	12	615	115	70	233	173	222	16.46	D	STD	36	40	18
SMF55D23L	12	615	115	70	233	173	222	16.46	C	STD	36	40	18
EUROPEAN AUTOMOTIVE													
SMF44	12	480	68	45	208	175	175	12.26	C	STD	36	40	18
SMF44H	12	400	68	44	208	174	190	12.67	C	STD	36	40	18
SMF53L	12	620	105	60	242	175	175	13.75	C	STD	36	40	18
SMF53R	12	620	105	60	242	175	175	13.75	D	STD	36	40	18
SMF55H	12	650	100	65	242	175	190	14.89	C	STD	36	40	18
SMF65L	12	670	120	75	277	175	175	15.76	C	STD	36	40	18
SMF65R	12	670	120	75	277	175	175	16.73	D	STD	36	40	18
SMF66H	12	780	160	85	277	175	190	18.72	C	STD	36	40	18
SMF66HR	12	780	160	85	277	175	190	18.72	D	STD	36	40	18
SMF75L	12	830	160	80	315	175	175	18.70	C	STD	36	-	18
SMF77H	12	820	170	95	315	175	190	19.85	C	STD	36	-	18
SMF85L	12	800	150	85	351	175	175	19.61	C	STD	36	-	18
SMF88H	12	900	200	105	351	175	190	21.97	C	STD	36	-	18
4WD/SUV/TRUCK AND INDUSTRIAL APPLICATION													
SMFNS70X	12	700	125	75	259	173	223	18.05	D	STD	36	-	18
SMFNS70LX	12	700	125	75	259	173	223	18.05	C	STD	36	-	18
SMFN70ZZX	12	765	165	85	304	173	224	21.40	D	STD	36	-	18
SMFN70ZZLX	12	765	165	85	304	173	224	21.40	C	STD	36	-	18
SMF86Z	12	950	200	110	330	172	237	26.51	H	STD	-	-	18
SMF86ZT	12	950	200	110	330	172	237	26.43	H	TS	-	-	18

NEW ZEALAND

AUCKLAND

72B Highbrook Dr East Tamaki

Auckland 09 975 8900

HAMILTON

61 Mahana Rd Tr Rapa

Hamilton 07 849 2002

WELLINGTON

33 Pito-One Road, Korokoro, Lower Hutt

Wellington 04 566 1054

NELSON

3/9 Nayland Road, Stoke

Nelson 03 547 4008

CHRISTCHURCH

3B/198 Springs Road, Hornby

Christchurch 03 349 9650

0800 188 122

www.superchargebatteries.co.nz

